



INSTANT MAGNETIC ELECTRIC WATER HEATER

- INSTANT HEAT IN 3 SECONDS, HOT WATER
- SMART CHIP, INSTANT HEAT: POWER
- SMART TEMPERATURE DISPLAY (STD)

GIFT ACCESSORIES



FACTORY DIRECT

- INSTANT HEAT IN 3 SECONDS, HOT WATER ON DEMAND
- SMART CHIP, INSTANT HEAT: POWER MEETS PRECISION.
- SMART TEMPERATURE DISPLAY (STD) INTERFACE



FACTORY DIRECT + DROPSHIPPING

Hot Water On Demand

HEATS UP IN 3 SECONDS

Electromagnetic Induction + Isolated Systems = 95% Efficiency, 100% Safety



⚡
KW
ADJUST

📈
TEMPERATURE
ADJUST

✓
100°F
LIMIT

💧
H/C
THERAPY

Next-Gen Electromagnetic Water-Electric Decoupling Technology (WEDT): Redefining Bathing Safety Standards

**Non-Contact Electromagnetic
Induction Heating Technology
with Fully Isolated Water-Electric
Systems (IEC 60335 Certified),
Achieving 100% Shock-Free Bathing Safety.**

**430 Stainless Steel Heating
Element: High-Temperature
Resistance up to 1200°C (2192°F)**

**High-Frequency Magnetic Coil
Converts Electrical Energy into
High-Frequency Magnetic Induction
via IGBT Module (Insulated Gate Bipolar
Transistor), Enabling Efficient Eddy
Current Generation.**



Electromagnetic Induction Heating Technology

"Converts electrical energy into a high-frequency electromagnetic field, inducing rapid molecular agitation within the magnetic conductor. This generates heat through internal friction of ferrous particles without direct electrical contact, achieving true water-electricity separation."



Smart Temperature Display (STD) Interface

Real-time monitoring of the operation status of the water heater; easy operation.



energy saving and electricity saving

Instant electric water heater, built-in inverter system, adapts heating power sensitively according to the real-time detected water inflow and water temperature data constant temperature and energy-saving.

The water outlet temperature can be set arbitrarily between 30°C-55°C (computer type).





Vertical
script

(Note: All size data are measured manually, with slight deviations.)

PRODUCT PARAMETERS



JS-JR-008

Product model

8500W

Rated power

4mm²

Power cord

1800V/5mA/1s

Electric strength

30-55°C

Set temperature

IPX4

waterproof level

220-240V

Rated voltage

50HZ-60HZ

Rated frequency

0.6MPa

Rated pressure

Product
size

325mm*475mm*80mm

GIFT ACCESSORIES

(Accessories may vary slightly in appearance due to different batches, please refer to the actual product.)

①



②



③



④



⑤



⑥



⑦



⑧



⑨



①Electric water heater (1 unit) ②Shower head (1 set)

③Pipe (2 pieces) ④Flow regulator

⑤Install bracket ⑥Ground fault circuit interrupter (1 piece)

⑦Pre-filter ⑧Small accessory pack

⑨Instruction manual (1 book)